

<What's in the box >

Digital G-Sensor Control Box x1 Vehicle Specific Harness x1 Double sided tape x1 Cable ties x2



CAUTION: When installing please insure engine is off and hand brake on. Please begin installation once this has been confirmed. This product is to be installed by a professional.

- ※ This product is to be installed with arrow pointing forward as shown below.
- ※ This product is to be installed horizontally, please do not install on an angle.

<INSTALLATION >

- ① Disconnect the battery
- ② Remove the center console and remove the factory G-Sensor connectors

BNR32

- ③ Remove the factory G-Sensor and remove from bracket. Install this product onto the factory bracket and secure with the double sided tape and cable ties provided.



R32 GT-R Factory G-Sensor



Digital G-Sensor secured to bracket

BCNR33 BNR34

- ③ Install this product on top of the factory G-Sensor securing with double sided tape and cable ties provided. Or, install by removing the factory G-Sensor as shown in BNR32 installation.



R34 GT-R Installation



R33 GT-R Installation

- ④ Please secure the Digital G-Sensor to the vehicle. Connect the vehicle specific harness to the factory connectors and re-attached the center console.

MANUFACTURED BY 

Do-Luck Co.,Ltd.

1-1-28 Daikan Yamato KANAGAWA

2420025 JAPAN